0191-2459029/2459255(Jmu)

*KASHMIR* 



Website: www.jkpolice.gov.in E-mail: phqik@nic.in

{Provision Section}

## **Clarification/Amendment Notice**

In pursuance to receipt of queries from various intending bidders, clarifications/amendments are hereby made as per Annexure "A-1" to e-NIT No 51 of 2020 dated 19.11.2020 floated by this Hqrs for the installation of CCTV Surveillance system at Raj **Bhawan** Srinagar. The intending firms may visit Govt. e-tender https://jktenders.gov.in/ tender id 2020\_DGPJK\_109603\_1 for further details.

Sourabh Prashar (JKPS) DySP(Provision-Transport) For Director General of Police, PHQ, J&K, Jammu

No: Prov-II/Elect-CCTV-01/2018-19/8757-65 Copy to the:-

Dated: 102/2021.

- - 1. Principal Secretary to Govt. Home Department J&K Jammu
  - 1. ADGP Security/Armed J&K Jammu
  - 2. All IsGP J&K Police ......for favour of information.
  - 3. Director Door Darshan Jammu/Srinagar and Station Director All India Radio Srinagar/Jammu for putting the notice on air for three consecutive days.
  - 5. Manager Government Press Srinagar / Jammu for publication of the Notice in Govt Gazette.
  - 6. AIG Communication PHQ J&K Jammu for information with the request to arrange publication of Notice in 02 widely circulated national and 02 State Dailies through information department.

7. S.Q e-Procurement PHQ, J&K for information and n/action.

8 S.O (IT) PHQ, J&K for posting the notice available on website of J&K Police.

DySP of Police (Provision-Transport) For Director General of Police,

PHQ, J&K, Jammu

## Clarifications/ Amendments to e-NIT 51 of 2020 (installation of CCTV Surveillance System at Raj Bhawan Srinagar

Annexure A-1

- 1. The camera shall be 5 MP 30 FPS Day & night Motorized Varifocal IR Bullet/Dome Camera.
- 2. Imaging Device: Should have 1/2.7" or better progressive scan and CMOS type.
- 3. Resolution: 2560(H)x 1920(V) or better.
- 4. Lens: should provide 2.8 mm to 12 mm varifocal lens.
- 5. Wide Dynamic Range (WDR): 120dB or better.
- 6. IR viewable length at Night should be 30 Meters or better.
- 7. Signal to Noise ratio: >=50db S/n ratio
- 8. The Server is not required and specifications for NVR are already mentioned in NIT
- 9. Impact Protection: IP 67 & IK10
- 10. Operating Temperature/Humidity: -20 to 60° C
- 11. Mandatory Certifications: UL/BIS/FCC/CE
- 12.PTZ requirement: should support 18X optical motorized Zoom and 12X digital zoom and configuration pre-set is removed.

13.The 3<sup>rd</sup> Category Switch (24 port L2 edge switch) mentioned in the specifications is not required.

Sourabh Prashar (JKPS)

DySP(Provision & Transport),

For Director General of Police, J&K- Srinagar.